

# Hammer drills

Exceptional performance



BH 21

BH 16 V



**New!**  
**Power through  
concrete + stone**

- Optimum drilling performance
- Robust design and galvanised surfaces ensure long service life
- Grip, cylinder and casings are made from cast stainless steel
- Air buffer minimises component wear during standby operation
- From model BH 11 available with power blowing system for blowing out the drill hole

	Model	Blow frequency	Air demand *)	Chuck – Shank		Weight	Impact force	Weighted sum acceleration value**)
		per min	m <sup>3</sup> /min			kg	Nm	m/s <sup>2</sup>
Grip	BH 8	3240	0.6	S 19 x 82.5	a)	8.4	10	21.5
	BH 8	3240	0.6	S 22 x 82.5	a)	8.4	10	21.5
	BH 11	2400	1.4	S 22 x 108	f)	15.5	21	24.8
T-grip	BH 16	2040	1.8	S 22 x 108	f)	18.0	33	28.5
	BH 21	2400	2.4	S 22 x 108	f)	22.8	40	16.5
T-grip Vibration damped	BH 16 V	2040	1.8	S 22 x 108	f)	22.9	33	4.9

\*) at 6 bar \*\*) as per ISO8662 a) = Retaining spring b) = Retaining cap c) = Cross-head cap d) = Retaining pin e) = Locking retaining cap f) = Retaining catch

Applicable drill sets are available separately: mono-block drill, chuck, drill bit



**KAESER KOMPRESSOREN GmbH**

P.O. Box 2143 – 96410 Coburg – GERMANY – Tel: +49 9561 640-0 – Fax: +49 9561 640130  
www.kaeser.com – e-mail: productinfo@kaeser.com